



UTILITY MANUFACTURING CO., INC.
700 MAIN STREET, WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

FAUCET STEM LUBRICANT

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure, or Accident - Call **INFOTRAC** - Day or Night: **1-800-535-5053**
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) **IMPORTANT:** Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name: CLEANING COMPOUND **CAS NO.:** MIXTURE
Chemical Family: PETROLEUM GREASE **UN/NA #:** N/A
DOT Hazard Class: NOI **DATE OF ISSUE:** 5/08

SECTION I - HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients:	CAS #	TLV/PEL	AGENCY	TYPE	SARA-313(% Range)
HYDROCARBON OILS	8020-83-5	N/E			
ZINC OXIDE*	1314-13-2	N/E			

* CONTAINS <3% OF A TOXIC CHEMICAL SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313, TITLE III IF S.A.R.A.

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Move person away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water and seek medical attention. For direct contact hold eyelids apart for at least 15 minutes. **Seek medical attention.**

SKIN CONTACT: Remove contaminated shoes and clothing and cleanse affected areas thoroughly by washing with mild soap and water. If irritation persists **seek medical attention.**

INHALATION: (breathing) Not expected to be a hazard under normal operating conditions..

INGESTION: (swallowing) If swallowed, seek emergency medical attention.

SECTION III - HEALTH HAZARDS / ROUTES OF ENTRY

EYE CONTACT: One or more components of this material may be an eye irritant.

SKIN CONTACT: Continuous contact with this material may cause drying of skin. Chemical itself is an irritant or sensitizer.

SKIN ABSORPTION: Symptoms of toxicity are not anticipated by this route.

INHALATION: (breathing) Not expected to be a hazard under normal operating conditions.

INGESTION: (swallowing) Ingestion of large quantities may cause the following: Irritation of digestive tract, signs of nervous system depression, such as headache, drowsiness, dizziness, loss of coordination, fatigue, and nausea.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION: If current ventilation practices are not adequate to maintain airborne concentrations below established exposure limits additional ventilation or exhaust systems may be required.

RESPIRATORY PROTECTION: The use of respiratory protection is advised when concentrates exceed the established exposure limits.

PROTECTIVE GLOVES: The use of gloves impermeable to the specific material handled is advised to prevent possible irritation.

EYE PROTECTION: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

SECTION V - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: (materials to avoid) This product is incompatible with: *Oxidizing agents, strong acids and bases*

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF LEAK OR SPILL. Spilled material may be absorbed by an appropriate absorbent

WASTE DISPOSAL METHOD: Dispose of product in accordance with local, county, state, and federal regulations.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Use good personal hygiene practices. Keep container closed.



UTILITY MANUFACTURING CO., INC.
 700 MAIN STREET, WESTBURY, NY 11590
 (516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

FAUCET STEM LUBRICANT

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Extinguish with dry chemical, CO₂, or a universal type foam.
FIRE AND EXPLOSION HAZARD: May decompose during contact with flames, heating elements, or in combustion engines releasing irritating gases
FIRE FIGHTING PROCEDURES: Wear appropriate protective equipment including respiratory protection as conditions. Stop spill/release if it can be done without risk. Water spray may be useful in minimizing or dispersing vapors and cooling equipment exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.

SECTION IX - PHYSICAL DATA

APPROXIMATE BOILING POINT (DEG F):	N/A	PER CENT VOLATILE:	NEGLIGIBLE
SPECIFIC GRAVITY (68 F):	.92	FLASH POINT (TCC, DEG F):	>320
RELATIVE EVAPORATION RATE (ESTIMATED):	NEGLIGIBLE	PER CENT SOLUBILITY IN WATER:	NEGLIGIBLE
VAPOR PRESSURE @20C mmHg (CALCULATED):	NEGLIGIBLE		

SECTION X - OTHER REGULATORY DATA

<u>SARA</u>	<i>SECTION</i> 302: NOT LISTED	<u>HMIS</u>	Health: 0
	<i>SECTION</i> 311 & 312: FIRE		Flammability: 1
	<i>SECTION</i> 313: See Section I.I		Reactivity: 0
<u>TSCA</u>	All components are in full compliance with the TSCA inventory.	<u>CALIFORNIA PROPOSITION 65</u>	NOT LISTED
<u>RCRA</u>	Waste material would be a D001	<u>CERCLA</u>	NOT LISTED

CARCINOGENICITY:
 NOT LISTED with NTP or IARC.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufactures and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.